


MACHINE SCREWS

MS24693 & MS24693C MACHINE SCREWS



FORMERLY AN 507) - These non-structural screws have a 100° counter-sunk flat head. Cadmium plated, Type 2, Class 3. Tensile strength 55,000 PSI. For both CAD plated and Stainless MS24693C are stainless steel.

Thread	Length	MS24693 Cad Plated P/N	Price Each	MS24693C Stainless P/N	Price Each
4-40	3/8	MS24693S4	\$0.06	MS24693C4	\$0.06
	7/16	MS24693S5	\$0.05	---	---
	1/2	MS24693S6	\$0.07	MS24693C6	\$0.06
	5/8	MS24693S7	---	MS24693C7	\$0.09
	1	MS24693S10	\$0.11	MS24693C10	\$0.08
6-32	1/4	MS24693S24	\$0.06	MS24693C24	\$0.06
	3/8	MS24693S26	\$0.07	MS24693C26	\$0.08
	7/16	MS24693S27	---	MS24693C27	\$0.07
	1/2	MS24693S28	\$0.07	MS24693C28	\$0.10
	5/8	MS24693S29	\$0.07	MS24693C29	\$0.08
	3/4	MS24693S30	\$0.08	MS24693C30	\$0.11
	7/8	MS24693S31	\$0.09	---	---
8-32	1	MS24693S32	\$0.09	MS24693C32	\$0.11
	1-1/2	MS24693S36	\$0.17	---	---
	2	MS24693S40	\$0.21	---	---
	1/4	MS24693S46	\$0.08	MS24693C46	\$0.09
	3/8	MS24693S48	\$0.08	MS24693C48	\$0.11
	7/16	MS24693S49	---	MS24693C49	\$0.09
	1/2	MS24693S50	\$0.10	MS24693C50	\$0.12
	5/8	MS24693S51	\$0.10	MS24693C51	\$0.12
	3/4	MS24693S52	\$0.09	MS24693C52	\$0.14
	7/8	MS24693S53	\$0.11	---	---
	1	MS24693S54	\$0.12	MS24693C54	\$0.13
	1-1/4	MS24693S56	---	MS24693C56	\$0.17
	1-1/2	MS24693S58	\$0.15	---	---
10-32	2	MS24693S62	\$0.35	---	---
	1/4	MS24693S268	\$0.11	MS24693C268	\$0.14
	3/8	MS24693S270	\$0.08	MS24693C270	\$0.09
	7/16	MS24693S271	---	MS24693C271	\$0.14
	1/2	MS24693S272	\$0.09	MS24693C272	\$0.15
	5/8	MS24693S273	\$0.12	MS24693C273	\$0.17
	3/4	MS24693S274	\$0.11	MS24693C274	\$0.19
	1	MS24693S276	\$0.14	MS24693C276	\$0.21
	1-1/4	MS24693S278	---	MS24693C278	\$0.22
	1-1/2	MS24693S280	\$0.16	---	---
	2	MS24693S284	\$0.44	---	---
1/4-28	2-1/2	MS24693-S286	\$0.60	---	---
	7/16	---	---	MS24693C293	\$0.26
	1/2	MS24693S294	---	MS24693C294	\$0.27
	5/8	MS24693S295	---	MS24693C295	\$0.42
	3/4	MS24693S296	\$0.16	---	---
1	---	---	MS24693C298	\$0.39	

AN525 WASHER HEAD SCREWS



High-strength machine screws fabricated from alloy steel per specification AMS6300. Tensile strength 125,000 PSI. Cadmium plated per QQ-P-416, Type II, Class 3. Cross-recessed head.

Dash No.	Length in.	Grip in.	Thread Size	Price
AN525-832R4	1/4	1/32	8-32	\$0.19
AN525-832R5	5/16	--	8-32	\$0.13
AN525-832R6	3/8	1/32	8-32	\$0.13
AN525-832R7	7/16	1/16	8-32	\$0.15
AN525-832R8	1/2	1/8	8-32	\$0.14
AN525-832R9	9/16	5/32	8-32	\$0.17
AN525-832R10	5/8	7/32	8-32	\$0.16
AN525-832R11	11/16	9/32	8-32	\$0.18
AN525-832R12	3/4	11/32	8-32	\$0.17
AN525-832R14	7/8	15/32	8-32	\$0.20
AN525-832R16	1	19/32	8-32	\$0.17
AN525-832R18	1-1/8	23/32	8-32	\$0.26
AN525-832R20	1-1/4	27/32	8-32	\$0.24
AN525-832R22	1-3/8	31/32	8-32	\$0.52
AN525-832R24	1-1/2	1-3/32	8-32	\$0.35
AN525-8R9	9/16	5/32	8/36	\$0.17
AN525-10R4	1/4	--	10-32	\$0.12
AN525-10R5	5/16	--	10-32	\$0.16
AN525-10R6	3/8	1/32	10-32	\$0.14
AN525-10R7	7/16	1/16	10-32	\$0.15
AN525-10R8	1/2	1/8	10-32	\$0.16
AN525-10R9	9/16	5/32	10-32	\$0.17
AN525-10-9 (Slotted)	9/16	5/32	10-32	\$0.17
AN525-10R10	5/8	7/32	10-32	\$0.16
AN525-10R11	11/16	9/32	10-32	\$0.16
AN525-10R12	3/4	11/32	10-32	\$0.15
AN525-10R14	7/8	15/32	10-32	\$0.23
AN525-10R16	1	19/32	10-32	\$0.22
AN525-10R18	1-1/8	23/32	10-32	\$0.34
AN525-10R20	1-1/4	27/32	10-32	\$0.30
AN525-10R22	1-3/8	31/32	10-32	\$0.28
AN525-10R24	1-1/2	1-3/32	10-32	\$0.29
AN525-416R6	3/8	1/32	1/4-28	\$0.58
AN525-416R7	7/16	1/16	1/4-28	\$0.52
AN525-416R8	1/2	1/8	1/4-28	\$0.54
AN525-416R9	9/16	5/32	1/4-28	\$0.54
AN525-416R10	5/8	7/32	1/4-28	\$0.49
AN525-416R12	3/4	11/32	1/4-28	\$0.56
AN525-416R14	7/8	15/32	1/4-28	\$0.76
AN525-416R16	1	19/32	1/4-28	\$0.63
AN525-416R18	1-1/8	23/32	1/4-28	\$1.84
AN525-416R20	1-1/4	27/32	1/4-28	\$0.96


AN526 MACHINE SCREWS

Truss-head non-structural machine screws made of carbon steel, cadmium plated. Minimum tensile strength 55,000 PSI. Available in slot head or Phillips recessed head.

Thread	Length	Phillips Part No.	Price Ea.	Slotted Part No.	Price Ea.
4-40	1/4	AN526-440R4	\$0.20	----	---
	3/8	AN526-440R6	\$0.07	----	---
	1/2	AN526-440R8	\$0.06	----	---
	5/8	AN526-440R16	----	----	---
	1	AN526-440R16	----	----	---
6-32	1/4	AN526-632R4	\$0.06	----	---
	5/16	AN526-632R5	\$0.06	----	---
	3/8	AN526-632R6	\$0.06	AN526-632-6	\$0.14
	7/16	AN526-632R7	\$0.06	----	---
	1/2	AN526-632R8	\$0.07	AN526-632-8	\$0.11
	9/16	AN526-632R9	\$0.08	----	---
	5/8	AN526-632R10	\$0.07	AN526-632-10	\$0.54
8-32	3/4	AN526-632R12	\$0.11	AN526-632-12	\$0.16
	7/8	AN526-632R14	\$0.09	----	---
	1	AN526-632R16	\$0.09	----	---
	1-1/2	AN526-632-R24	\$0.17	----	---
	2	AN526-632R32	\$0.20	----	---
	1/4	AN526-832R4	\$0.08	----	---
	5/16	AN526-832R5	\$0.10	----	---
	3/8	AN526-832R6	\$0.09	----	---
	7/16	AN526-832R7	\$0.08	----	---
	1/2	AN526-832R8	\$0.09	AN526-832-8	\$0.46
	9/16	AN526-832R9	\$0.09	----	---
	5/8	AN526-832R10	\$0.09	----	---
	3/4	AN526-832R12	\$0.12	AN526-832-12	\$0.24
10-32	7/8	AN526-832R14	\$0.12	----	---
	1	AN526-832R16	\$0.11	AN526-832-16	\$0.19
	1-1/4	AN526-832-R20	\$0.19	----	---
	1-1/2	AN526-832-R24	\$0.29	----	---
	1/4	AN526-1032R4	\$0.11	----	---
	5/16	AN526-1032R5	\$0.08	----	---
	3/8	AN526-1032R6	\$0.10	----	---
	7/16	AN526-1032R7	\$0.09	----	---
	1/2	AN526-1032R8	\$0.11	----	---
	9/16	AN526-1032R9	\$0.10	----	---
	5/8	AN526-1032R10	\$0.11	AN526-1032-10	\$0.26
	3/4	AN526-1032R12	\$0.13	AN526-1032-12	\$0.13
	7/8	AN526-1032R14	\$0.12	AN526-1032-14	---
	1	AN526-1032R16	\$0.16	----	---
	1-1/8	AN526-1032R18	\$0.13	----	---
1-1/4	AN526-1032R20	\$0.16	----	---	
1-1/2	AN526-1032R24	\$0.29	----	---	
1-3/4	AN526-1032R28	\$0.28	----	---	
2	AN526-1032R32	\$0.52	----	---	

AN526C STAINLESS STEEL MACHINE SCREWS

Stainless steel Phillips and slotted, Use slotted screws for antiques.



Thread	Length	Phillips Part No.	Price Ea.	Slotted Part No.	Price Ea.
4-40	1/2	AN526C-440R8	\$0.08	----	---
	1/4	AN526C-632R4	\$0.08	AN526C-632-4	\$0.33
	3/8	AN526C-632R6	\$0.10	----	---
6-32	1/2	AN526C-632R8	\$0.09	AN526C-632-8	\$0.20
	5/8	AN526C-632R10	\$0.11	AN526C-632-10	\$0.30
	3/4	AN526C-632R12	\$0.10	----	---
	1	AN526C-632R16	\$0.13	AN526C-632-16	\$0.29
8-32	1/4	AN526C-832R4	\$0.14	----	---
	3/8	AN526C-832R6	\$0.11	----	---
	1/2	AN526C-832R8	\$0.12	AN526C-832-8	\$0.20
	5/8	AN526C-832R10	\$0.13	AN526C-832-10	\$0.30
	3/4	AN526C-832R12	\$0.14	AN526C-832-12	\$0.34
10-32	1	AN526C-832R16	\$0.16	AN526C-832-16	\$1.50
	1/4	AN526C-1032R4	\$0.38	----	---
	3/8	AN526C-1032R6	\$0.14	AN526C-1032-6	\$0.28
	1/2	AN526C-1032R8	\$0.14	AN526C-1032-8	\$0.24
	5/8	AN526C-1032R10	\$0.18	AN526C-1032-10	\$0.20
	3/4	AN526C-1032R12	\$0.19	AN526C-1032-12	---
	1	AN526C-1032R16	\$0.21	----	---
1/4-20	1-1/4	AN526C-1032R20	----	----	---
	1-1/2	AN526C-1032R24	\$0.28	----	---
	1/2	AN526C-420R8	\$1.57	----	---
1/4-28	1/2	AN526C-428R8	\$0.37	----	---
	3/4	AN526C-428R12	\$0.42	----	---
1-1/8	----	---	----	AN526C-428-18	\$0.69

Note: Some sizes of AN526C screws are furnished as commercial equipment as AN screws are no longer available.

HA